



PHILIPS

Indoor Lighting

GreenPerform Highbay
BY698P G2



Competitive industry solution with well accepted look & feel

Following the success of GreenPerform Highbay families, GreenPerform Highbay NEW GEN is continuously exploring a better price & performance balance. The product family offers wide product ranges, competitive enough SPEC with long term quality & reliability, covering most of the potential industrial applications.

Features and benefits

- Strong energy saving story
- Better & easier on site calibration
- Robust & Reliable with a long service lifetime
- Various application requirements satisfied with complete product family


Application

- General manufacturing
- Warehouses & logistical centers
- Exhibition halls & high ceiling lounges


Product Data

| Types (BY698P G2) | LED68 | LED105 | LED155 | LED205 | LED265 |
|--------------------------|--|---------|---------|---------|---------|
| Lumen Output (typ.) | 6800lm | 10500lm | 15500lm | 20500lm | 26500lm |
| System Power – PSU(typ.) | 52W | 78W | 115W | 149W | 192W |
| System efficacy | Typ. 130lm/W – 6800lm version Typ. 135lm/W – other lumen versions | | | | |
| CCT (typ.) | CW (6500K)/ NW (4000K) | | | | |
| CRI | > 80 | | | | |
| Color consistency | 5 SDCM | | | | |
| IP/IK rating | IP65/ IK08 | | | | |
| Classification | Class I | | | | |
| Operation Temperature | -30°C to +50°C (Ta35°C) | | | | |
| Lifetime (hrs) | 50,000 hrs (Calculated L70B50) @35°C | | | | |
| Optics | WB; NB | | | | |
| Input Voltage | 220-240V, 50/60 Hz | | | | |
| Power factor | 0.95 | | | | |
| Surge projection | 2KV/4KV | | | | |
| THD | <20% - 6800lm version <15% - other lumen version | | | | |
| Mounting / Installation | Hook (included in the box for GM version, NOT included in the box for GC version); Optional: Pipe; Bracket | | | | |
| Housing | Aluminum die-casting | | | | |
| Diameter (mm) | Φ307 | Φ307 | Φ307 | Φ360 | Φ416 |
| Height (mm) | 99 | 99 | 99 | 99 | 99 |
| Weight (KGS) | 2.5 | 2.5 | 2.5 | 3.2 | 4.0 |
| Certificate | CCC/CB/EMC/CE LM79 for key runner | | | | |

Photometry



WB



NB

Order Information

| 12NC | Description | Specification |
|--------------|-------------------------------|---|
| 911401516661 | BY698P LED68/CW PSU NB GM G2 | 52W, 6800lm, 6500K, fixed output, narrow beam |
| 911401516761 | BY698P LED68/CW PSU WB GM G2 | 52W, 6800lm, 6500K, fixed output, wide beam |
| 911401516861 | BY698P LED68/NW PSU NB GM G2 | 52W, 6800lm, 4000K, fixed output, narrow beam |
| 911401516961 | BY698P LED68/NW PSU WB GM G2 | 52W, 6800lm, 4000K, fixed output, wide beam |
| 911401517061 | BY698P LED105/CW PSU NB GM G2 | 78W, 10500lm, 6500K, fixed output, narrow beam |
| 911401517161 | BY698P LED105/CW PSU WB GM G2 | 78W, 10500lm, 6500K, fixed output, wide beam |
| 911401517261 | BY698P LED105/NW PSU NB GM G2 | 78W, 10500lm, 4000K, fixed output, narrow beam |
| 911401517361 | BY698P LED105/NW PSU WB GM G2 | 78W, 10500lm, 4000K, fixed output, wide beam |
| 911401517461 | BY698P LED155/CW PSU NB GM G2 | 115W, 15500lm, 6500K, fixed output, narrow beam |
| 911401517561 | BY698P LED155/CW PSU WB GM G2 | 115W, 15500lm, 6500K, fixed output, wide beam |
| 911401517661 | BY698P LED155/NW PSU NB GM G2 | 115W, 15500lm, 4000K, fixed output, narrow beam |
| 911401517761 | BY698P LED155/NW PSU WB GM G2 | 115W, 15500lm, 4000K, fixed output, wide beam |
| 911401517861 | BY698P LED205/CW PSU NB GM G2 | 149W, 20500lm, 6500K, fixed output, narrow beam |
| 911401517961 | BY698P LED205/CW PSU WB GM G2 | 149W, 20500lm, 6500K, fixed output, wide beam |
| 911401518061 | BY698P LED205/NW PSU NB GM G2 | 149W, 20500lm, 4000K, fixed output, narrow beam |
| 911401518161 | BY698P LED205/NW PSU WB GM G2 | 149W, 20500lm, 4000K, fixed output, wide beam |
| 911401518261 | BY698P LED265/CW PSU NB GM G2 | 192W, 26500lm, 6500K, fixed output, narrow beam |
| 911401518361 | BY698P LED265/CW PSU WB GM G2 | 192W, 26500lm, 6500K, fixed output, wide beam |
| 911401518461 | BY698P LED265/NW PSU NB GM G2 | 192W, 26500lm, 4000K, fixed output, narrow beam |
| 911401518561 | BY698P LED265/NW PSU WB GM G2 | 192W, 26500lm, 4000K, fixed output, wide beam |

Accessories to be released soon:

| | | |
|--------------|-----------------------|---|
| 911401523161 | BY698Z R-AL S G2 | BY698P LED68/105/155 G2 |
| 911401523261 | BY698Z R-AL M G2 | BY698P LED205 G2 |
| 911401523361 | BY698Z R-AL L G2 | BY698P LED265 G2 |
| 911401523461 | BY698Z PSU MB G2 | Mounting bracket for PSU version. |
| 911401565101 | BY698Z hook accessory | Included in the GM packaging box, but NOT included in the GC packaging box. |

© 2018 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

<http://www.lighting.philips.com>

